

destroyit®

BUSINESS SHREDDERS

→ 3 0 CENTRALIZED OFFICE SHREDDER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | wide, 16" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs | lifetime warranty on the cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy "twin drive system" with dust-proof gear box housing | high quality wooden cabinet mounted on casters | convenient shred bin | 44 gallon shred volume

Dimensions (D x W x H): 23 1/4 x 25 1/4 x 38 1/4 inches, Shipping weight: 232 lbs. (strip-cut) / 233 lbs. (cross-cut).



Oversized, multifunction control element uses integrated optics to indicate operational status.

CONVENIENT SHRED BIN



A large capacity shred bin makes bags optional.

→ 3 STRIP-CUT

Strip width 1/4" (6 mm)
 Sheet capacity 22-25*
 Security level 2
 Feed opening 16"
 Max. horsepower 1

→ 3 CROSS-CUT

Particle size 3/16" x 1 1/2" (4 x 40 mm)
 Sheet capacity 20-22*
 Security level 3
 Feed opening 16"
 Max. horsepower 1

→ 3 CROSS-CUT

Particle size 3/32" x 5/8" (2 x 15 mm)
 Sheet capacity 12-14*
 Security level 4
 Feed opening 16"
 Max. horsepower 1

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 5/2011.



3134 Industry Drive
 North Charleston, South Carolina 29418
 800-223-2508, fax: 843-552-2974
 www.mbmcorp.com



1675 Sismet Road, unit 4
 Mississauga, Ontario L4W 4K8
 800-387-2528, fax: 905-840-1114
 www.ideal-mbm.com

Dealer:

For More Info

Click Here --->

