

Triumph®

by **IEAL**

For More Info



➔ **4250**

Click Here --->

“SCS” (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade and clamp drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | automatic clamp | side guide with measuring scale | spindle-guided back gauge with calibrated crank | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | optional stand or cabinet (shown)

Dimensions (D x W x H): 27 ¼ x 25 ¼ x 14 ⅞ inches (41 ½ H with stand, 42 ½ H with cabinet),
Shipping weight: 191 lbs. (217 with stand, 278 with cabinet).



A digital measurement readout ensures exact positioning of back gauge.



The hinged, transparent front safety guard is electronically secured.



The blade changing device covers edge of blade for safe handling.

➔ **4250**

Cutting width	16 ⅞"
Cutting height	1 ½"
Narrow cut	1 ⅜"
Cutting length behind blade	15 ⅞"
Table length in front of blade	9"
Motor	3/5 hp
Power supply	115 V, 60 Hz

Dealer:



3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com



1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com